

# 内包骨架无弹簧油封



代号	名称	截面图	材料	压力	温度	圆周速度	特点
VC	内包单唇 无弹簧油封		橡胶+骨架	0	NBR -40至100	≤6	外圆周面为橡胶, 可装 配软、硬基座, 无防尘唇 不能承压密封
					FKM -20至200	≤10	
KC	内包双唇 无弹簧油封		橡胶+骨架	0	NBR -40至100	≤6	外圆周面为橡胶, 可装 配软、硬基座, 有防尘唇 不能承压密封
					FKM -20至200	≤10	

d	D	H	d	D	H	d	D	H	d	D	H	d	D	H
10	20	4	22	47	7	30	52	5	45	68	6	63	80	7
10	25	5	23	32	7	30	55	5	45	68	9	65	85	9
12	22	4	23	42	6	30	56	5	45	70	6	65	88	5
12	25	5	24	38	5	32	45	5	45	72	6	65	88	6
12	30	6	24	40	6	32	48	6	48	62	6	68	90	7
12	32	5	24	47	5	32	52	5	48	62	8	70	88	7
13	28	5	25	35	5	34	54	8	48	65	7	70	90	10
14	24	6	25	38	5	35	47	5	48	70	6	70	92	5
14	28	5	25	40	5	35	48	5	50	65	6	70	92	7
14	34	6	25	40	6	35	50	5	50	68	7	70	92	12
15	25	4	25	41	6	35	50	6	50	72	5	70	95	7
15	30	4	25	42	5	35	52	5	50	72	6	74	95	7
15	30	5	25	45	5	35	55	5	50	72	9	75	100	7
15	32	6	25	45	7	35	55	8	50	80	6	75	100	8
15	35	6	25	47	5	35	60	5	50	80	7	80	95	6
16	24	4	25	47	6	35	62	6	52	65	6	80	100	7
16	30	5	25	50	5	38	54	6	52	70	7	80	105	7
17	30	7	26	40	5	38	55	6	52	75	9	80	110	7
17	32	6	26	42	6	38	58	5	55	70	6	85	100	9
17	35	5	26	48	6	38	58	8	55	72	7	85	105	9
18	35	6	27	42	7	40	52	5	55	78	9	85	110	7
18	38	7	27	47	8	40	55	5	56	70	6	90	115	5
19	35	6	28	40	5	40	58	6	58	72	6	90	115	13
20	32	5	28	45	6	40	60	5	58	75	7	95	115	9
20	34	5	28	47	5	40	62	5	58	80	6	95	120	8
20	35	6	28	48	6	40	62	6	58	80	9	95	135	13
20	40	5	28	50	6	40	62	8	60	75	6	100	125	8
20	40	7	30	40	5	40	65	5	60	78	7	110	140	8
20	42	6	30	42	5	40	65	6	60	82	6	112	130	7
21	40	7	30	45	6	42	55	6	60	82	9	115	135	8
22	34	5	30	46	5	42	60	7	60	85	6	135	165	14
22	35	5	30	48	6	42	65	9	60	90	7	140	170	14
22	38	6	30	50	5	45	60	6	62	75	6	220	255	12
22	42	5	30	50	8	45	62	7	62	85	6	240	280	15