


内置式骨架防尘圈 F8



装配例



型式例

截面图	材料	温度范围	速度	特点	代号
	NBR FKM PU	-30至100 -20至200 -35至100	1	外骨架紧配合， 防尘效果好，结 构小型化	F8

尺寸	公差
φ D1	H8
L1	±0.2

d1	D1	L1	d1	D1	L1	d1	D1	L1	d1	D1	L1	d1	D1	L1
1/2	11/16	3/32	1-3/4	2-3/8	1/4									
1/2	3/4	1/8	1-3/4	2-5/8	1/4									
5/8	15/16	3/16	1-7/8	2-1/4	3/16									
5/8	7/8	1/8	1-7/8	2-1/2	1/4									
3/4	1-1/4	1/4	2	2-3/8	3/16									
3/4	1	1/8	2	2-5/8	1/4									
7/8	1-1/8	1/8	2	2-1/2	1/4									
7/8	1-1/4	3/16	2	2-3/4	1/4									
1	1-1/4	1/8	2	2-7/8	15/32									
1	1-3/8	3/16	2-1/8	2-1/2	3/16									
1	1-7/16	1/4	2-1/4	2-5/8	1/4									
1	1-1/2	3/16	2-1/4	2-3/4	1/4									
1	1-5/16	1/8	2-1/4	2-7/8	1/4									
1-1/16	1-1/2	3/16	2-3/8	3	1/4									
1-1/8	1-1/2	3/16	2-1/2	3	1/4									
1-1/8	1-3/8	1/8	2-1/2	3-1/8	1/4									
1-1/8	1-9/16	1/4	2.66	3-1/4	3/8									
1-1/8	1-5/8	1/4	2-3/4	3-1/4	1/4									
1-1/4	1-1/2	1/8	2-3/4	3-1/8	3/16									
1-1/4	1-11/16	3/16	2-3/4	3-3/4	3/8									
1-1/4	1-3/4	1/4	3	3-1/2	1/4									
1-1/4	1-7/8	1/4	3	3-3/4	1/4									
1-1/4	1-5/8	1/4	3-1/2	4	1/4									
1-3/8	1-3/4	3/16												
1-3/8	1-7/8	1/4												
1-3/8	1-5/8	1/8												
1-1/2	1-7/8	1/4												
1-1/2	1-7/8	3/16												
1-1/2	2	1/4												
1-5/8	2-1/8	1/4												
1-5/8	2-5/8	1/4												
1-3/4	2-1/8	3/16												
1-3/4	2-1/4	1/4												